

EARTHKEEPER® EP BIODEGRADABLE EXTREME PRESSURE GREASE

Earthkeeper® EP is a high performance lubricating grease based on calcium sulfonate thickener and a blend of biodegradable oils. This extreme pressure grease is suitable for a wide range of applications, including equipment under severe load, shock load, and vibrations.

Besides offering excellent wear protection, Earthkeeper® EP protects bearings from water, including acidic and caustic solutions. Earthkeeper® EP continues to protect long after conventional greases have become too waterlogged and soft to be of any value. The rust protection is second to none, greatly extending the life of bearings exposed to brine or other corrosive materials.

Earthkeeper® EP grease meets the definition of a biobased lubricant as outlined in section 9001 of The Farm Security and Rural Investment Act (FSRIA) of 2002 (Public Law 107-171/ HR 2642) and qualifies for preferred procurement by U.S. Federal Agencies as set forth in FSRIA section 9002.

BENEFITS:

- **BIODEGRADABLE** – easily passes all tests for biodegradability and is classified as “Readily Biodegradable”.
- **WEAR PROTECTION** – suitable for use on highly loaded equipment.
- **WATER RESISTANCE** – resists being flushed out of the bearing.
- **RUST RESISTANCE** – outstanding protection.

APPLICATIONS:

Use Earthkeeper® EP in all industrial bearings, earthmoving and mining equipment. It is especially useful in ecologically sensitive areas and in marine equipment.

ASTM #		TYPICAL CHARACTERISTICS
	Grade	EP 2
D-217	Cone Penetration (Worked)	265-295
D-2265	Dropping Point, °F (°C)	532 (278)
D-445	Kinematic Viscosity (Base Oil with Polymer) cSt @ 40°C cSt @ 100°C	220.0 49.0
Gardner Method	Density, lb/gal @ 60°F (15.5°C) Specific Gravity, g/cc @ 60°F (15.5°C)	8.61 1.03
D-2596	Four Ball EP Weld Point, kg	500
D-2266	Four Ball Wear Scar Width, mm	0.60
D-1264	Water Washout, % Loss	4
	Thickener Type	Calcium Sulfonate
OEM Standard	Low Temperature Pumpability Lincoln Ventmeter @ 400 psi, °F (°C)	30 (-1)
	Operating Temperature Range	30 (-1) to 250 (120)
FTM 321.2	Screen Bleed, % Loss	1.5

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Shuttle Tanks	Nonreturnable Totes	Drums	Pails
---------------	---------------------	-------	-------

For warranty information, scan the QR code.
You can also email us at sales@whitmores.com
Or write to the Sales Department at the address below.

930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318
An ISO 9001 and ISO 14001 registered company • www.whitmores.com

