

1203 Element



Description

- Removes Contaminates as low as 1 Micron
- Removes Water and Dirt
- Does not remove or deplete additives

Used For

- Engine Oil
- Transmission Oil
- Hydraulic Oil
- Cutting Oil
- Other Oil Based Lubricants

Filter Capacity

- Requires 56 qt/53 L Additional Makeup Fluid Per Housing

Specifications

- Beta₃=250
- Fits 1200 Size Housing
- Overall Dimensions
10.25" Height
11" Diameter
- Max Reservoir Size
Lube 22.1-88 Gal/83.29-333.12 L *Per Filter Set
Hydraulic/Gear 250.1-1000 Gal/946.36-3785.41 L *Per Filter Set
- Flow Rate 5-20 GPM/18.93-75.7 LPM

Notes

- Flow Rates are Established using ISO 32-68 Viscosity Oils at the Standard 40° C/104° F and are subject to vary
- Viscosity, operating temp, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, elements need to be changed between 500-1000 hours for optimal performance or when the flow is half the starting flow
- *The Max Dirt & Water Capacities (Per Filter Set of 3 Filters) are determined when the flow is reduced by half the original flow. (this is the optimal operating conditions)*
- Used with Petroleum or Synthetic Fluids

Recommended Viscosities

- Viscosity 32-68
- SAE 20