



Harvard
Corporation

1206 Element



Description

- Removes Contaminates as low as 1 Micron
- Removes Water and Dirt
- Does not remove or deplete additives

Used For

- Engine Oil
- Transmission Oil
- Hydraulic Oil
- Cutting Oil
- Other Oil Based Lubricants

Filter Capacity

- Requires 56 qt/53 L Additional Makeup Fluid Per Housing

Specifications

- Beta₃=250
- Fits 1200 Size Housing
- Overall Dimensions
 - 15.25" Height
 - 11" Diameter
- Max Operating Pressure 125 PSI
- Max Reservoir Size
 - Lube 22.1-88 Gal/83.29-333.12 L *Per Filter Set
 - Hydraulic/Gear 250.1-1000 Gal/946.36 3785.41 L *Per Filter Set
- Flow Rate 2-12 GPM/15.14-45.42 LPM

Notes

- Flow Rates are Established using ISO 220-680 Viscosity Oils at the Standard 40° C/104° F and are subject to vary
- Viscosity, operating temp, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, elements need to be changed between 500-1000 hours for optimal performance or when the flow is half the starting flow
- *The Max Dirt & Water Capacities (Per Filter Set of 2 Filters) are determined when the flow is reduced by half the original flow. (this is the optimal operating conditions)
- Used with Petroleum or Synthetic Fluids

Recommended Viscosities

- Viscosity 220-680
- SAE 50